Ministry of investment

CCTV System Specification

✤ <u>BOQ:</u>

No	Description	QTY	Comply Yes/No	Notes			
	CCTV System						
1	Indoor Fixed (Dome) Camera	104					
2	Outdoor Fixed (Bullet) Camera	20					
3	Network video Recorder 64 Chanel	2					
Network Connections							
1	Edge Switches	6					
<u>2</u>	Patch panel	6					
<u>3</u>	<u>Cabinet</u>	6					
<u>4</u>	installations	Per meter					

* <u>Specifications:</u>

1) Indoor Fixed (Dome) Camera (104 QTY):

Description	QTY	Comply Yes/No	Notes
Resolution	Minimum 5MP		
Image Sensor	1/2.7" progressive CMOS		
IR Distance	Minimum IR distance: 30 m		
Stream	Minimum 2 Streams		
Iris Type	Fixed		
Min. Illumination	0.007 Lux or less @ F1.4		
Compression	H.265+, H.264+, H.264		
WDR	120 dB		

Focal Length	2.8mm,4mm	
Power Supply	12V DC/POE	
Protection Grade	IP67	
	smart Motion Detection,	
Al Support	tripwire, video tampering	
	alarm and intrusion	
ONVIF	ONVIF (Profile S/Profile	
	G/Profile T)	

2) Outdoor Fixed (Bullet) Camera (20 QTY):

Description	QTY	Comply Yes/No	Notes
Resolution	Minimum 8MP		
Image Sensor	1/2.7" progressive CMOS		
IR Distance	Minimum IR distance: 40 m		
Stream	Minimum 2 Streams		
Iris Type	Fixed		
Min. Illumination	0.004 Lux or less @ F1.1		
Compression	H.265+, H.264+, H.264		
WDR	120 dB		
Focal Length	2.6mm or 13.5mm		
Power Supply	12V DC/POE		
Protection Grade	IP67		
	smart Motion Detection,		
Al Support	tripwire, video tampering		
	alarm and intrusion		
ONVIF	ONVIF (Profile S/Profile		
UNVIF	G/Profile T)		

3) <u>Network video Recorder 64ch (2 QTY):</u>

Description	QTY	Comply Yes/No	Notes
IP Camera Input	64 CHANEL		
Internal HDD	8 SATA HDD		
HDD	Recording for minimum 30 days		
עשא	on full detection		
Bandwidth	Min 400Mbps		
4K Up to 12MP Resolut	ion for Preview and Playback		
Support	Mobile App, Web		
	1 HDMI out, 1 VGA out, USB,2		
Auxiliary Interface	port RJ-45 Port		
	(10/100/1000Mbps)		
P2P	Support P2P		
ONVIF	Support		
Raid	RAID 0/1/5/6/10		
Multiple-channel Playback	Max. 16-channel playback		
	Face detection and recognition,		
AI by Camera support	SMD plus, perimeter		
A by Callera Support	protection, ANPR, Heat Map,		
	People counting, metadata		

4) Cabling specs:

	Item	Otv	Comply Yes/No	Notes
	Switches	Qty		
1	24 Port Gigabit Ethernet PoE Switch with 2 Uplink Gigabit Port & 2 SFP Port with Transceivers, Unmanaged, Rack Mountable, 1U	6		
	Fiber & Copper Cables Work			
1	CAT6 24 Port Patch Panel Fully Loaded – Metal – Snap in Jacks	6		
2	CAT6 Patch Cords 1m - LSZH	126		

3	Cat6 for cameras and NVRs Includes - Pipes/Trunks - Cat6 Cable per meter	126	
4	Pulling, Termination, Labeling and Testing	126	
5	Optional: Cable Organizer	6	
6	Camera Tester support camera type in this tender with HDMI (in, out) Li-Ion battery or PoE+ , Connect to any IP or analog camera using RJ-45, supports all power requirements for IP and analog cameras micro SD, data cable testing	1	
7	Fiber Cable Pulling uplinks for each switch per meter		

5) Special Requirements:

- The company must be operating within the Hashemite Kingdom of Jordan for a period of no less than five years, with attached evidence of that.
- Installation requirements: installation and configuration for devices supplies, NVR configuration and Network Cable wiring termination, testing, labeling and training.
- Install poles for cameras for outdoor cameras and all accessories when needed.
- 3 Years Warranty for the proposed solution from project handing over.
- 3 Years free maintenance include (4) preventive visits per year.
- Minimum 5 similar projects in same field similar Ministry of Investment attached evidence in technical offer.
- The tenderer shall submit all the materials and works required in List No. (3), provided that all materials are of the same type and of known quality.
- Company and Technical certificates are required.
- The supplier must be an authorized agent for the supplied devices.